

BRENTWOOD STORMTANK[®] MODULE 25

You can restrict the discharge rate of your stormwater runoff and reduce backfill with StormTank® Module systems. StormTank® Module systems achieve these restrictions by providing large-volume storage and incorporating an impermeable liner to prevent infiltration.

Layfield's line of subsurface stormwater storage units can be flexibly designed to meet your specific site requirements and achieve compliance with strict runoff regulations. Without sacrificing storage capacity, StormTank® Modules allow a project to use fewer total units. Their quick assembly reduces installation costs and makes StormTank® an ideal solution for stormwater management.

The StormTank® Module 25 Series is a subsurface stormwater storage unit, load-rated for extreme applications, like heavy trucks or under fire access roads.

April 2023 Style	Brentwood StormTank [®] Module 25				
	Size (L x W x H in inches)	VOID SPACE (%)	MODULE STORAGE	INSTALLED Storage	WEIGHT
ST- 12	36in x 18in x 12in	93.70%	4.21 ft ³ 0.12 m ³	6.91 ft ³ 0.20 m ³	17.56 lbs 7.97 kg
ST-18	36in x 18in x 18in	95.5%	6.54 ft ³ 0.18 m ³	9.15 ft ³ 0.26 m ³	22.70 lbs 10.30 kg
ST-24	36in x 18in x 24in	96%	8.64 ft ³ 0.24 m ³	11.34 ft ³ 0.32 m ³	26.30 lbs 11.93 kg
ST-30	36in x 18in x 30in	96.5%	10.86 ft ³ 0.31 m ³	13.56 ft ³ 0.38 m ³	29.50 lbs 13.38 kg
ST-33	36in x 18in x 33in	96.9%	11.99 ft ³ 0.34 m ³	14.69 ft ³ 0.42 m ³	31.30 lbs 14.20 kg
ST-36	36in x 18in x 36in	97%	13.10 ft ³ 0.37 m ³	15.80 ft ³ 0.45 m ³	33.10 lbs 15.01 kg

Disclaimer: Layfield disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

For up-to-date technical information, be sure to visit us online at www.LayfieldGroup.com



Nite10