

## **ENVIROSLOPE® WIRE MESH FACE**

EnviroSlope® Wire Mesh Face is an economical system to create attractive vegetated reinforced soil slopes up to 70 degrees or Stone faced MSE walls up to 90 degrees.

	April 2023	Wire Mesh Panel				
	Item	ASTM	Size			
	Panel Wire	A82	Diameter 5.7 mm /.22 inch			
Properties	Panel Mesh	-	100 mm X 100 mm / 4 inch X 4 inch			
per	Strut Wire	A82	Diameter 6.2 mm / 0.24 inch			
	Galvanizing	A123	Thickness 0.087 mm / 3.4 mil			
eria	Panel length		3000 mm / 9.84 feet			
Material	Panel Height		450 mm / 1.47 feet			

	April 2023		Mirafi Uniaxial Geogrids -Metric Values									
		ASTM	2XT <sup>2</sup>	3XT	5XT	7XT	8XT	10XT	20XT	22XT	24XT	
Material Properties	Wide Width (kN/m) MD	D6637 Ultimate	29	51	68	86	108	139	200	300	400	
	Creep Reduced Strength(kN/m )	D5262	18	32	43	55	68	88	127	190	253	
	LTDS (kN/m)1	GRI GG4	(b)									
	Sand, Silt, Clay1		16	28	38	47	59	76	110	164	219	
	Roll Width (m)		3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	
	Roll Length (m)		46	46	46	61	61	61	61	61	61	
	Roll Weight(kg)		46	54	56	75	85	107	157	226	261	

Note1 Refer to manufacturers Long Term Design Strength (LTDS) Reduction factors listed on Layfield website.

Note2 Values shown for 2XT are both machine and cross-machine direction. Values for other products are machine direction only.

**Disclaimer**: Layfield disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

For up-to-date technical information, be sure to visit us online at www.LayfieldGroup.com

